

# Commercial Lighting Program

## Eligible Product List



\*Manitoba Hydro is a licensee of the Trademark and Official Mark.

### COMPACT FLUORESCENT (CF) LIGHTING SYSTEMS - HARD-WIRED DIMMABLE BALLASTS

Manufacturer	Model Number	Category	Voltage	Input Power	Lamp	Min Temp (°C)	Min Dim	Type	Case	IR	Test Year	Warranty	Control Type
Advance	IZT-2S26-M5-LD	LH	120V	19,34	2x13W	10	3%	P	NP	NT	2010	5 yrs	0-10V
Advance	IZT-2S26-M5-LD	LH	277V	19,34	2x13W	10	3%	P	NP	NT	2010	5 yrs	0-10V
Advance	IZT-2S26-M5-LD	LH	120V	6,18	1x13W	10	3%	P	NP	NT	2010	5 yrs	0-10V
Advance	IZT-2S26-M5-LD	LH	277V	6,18	1x13W	10	3%	P	NP	NT	2010	5 yrs	0-10V
Advance	IZT-2S26-M5-LD	LH	120V	13,55	2x26W	10	3%	P	NP	NT	2010	5 yrs	0-10V
Advance	IZT-2S26-M5-LD	LH	277V	13,55	2x26W	10	3%	P	NP	NT	2010	5 yrs	0-10V
Advance	IZT-2S26-M5-LD	LH	120V	8,30	1x26W	10	3%	P	NP	NT	2010	5 yrs	0-10V
Advance	IZT-2S26-M5-LD	LH	277V	8,30	1x26W	10	3%	P	NP	NT	2010	5 yrs	0-10V
Advance	IZT-2S26-M5-LD	LH	120V	9,47	1x42W	10	3%	P	NP	NT	2010	5 yrs	0-10V
Advance	IZT-2S26-M5-LD	LH	277V	9,47	1x42W	10	3%	P	NP	NT	2010	5 yrs	0-10V
Advance	IZT-2T42-M2-LD	SH	120V	19,43	2x42W	10	3%	P	P	NT	2009	5 yrs	0-10V
Lutron	FDB-T426-120-1-S	LH	120V	31	1x26W	10	5%	P	P	NT	2009	3 yrs	3 Wire
Lutron	FDB-T426-120-2-S	LH	120V	60	2x26W	10	5%	P	NP	Free	2006	5 yrs	3 Wire
Lutron	FDB-T432-120-1-S	LH	120V	37	1x32W	10	5%	P	NP	Free	2006	3 yrs	3 Wire
Lutron	FDB-T442-120-2-S	LH	120V	90	2x42W	10	5%	P	P	O	2009	5 yrs	3 Wire

Category: LH= Low Harmonics, SH = Standard Harmonics

Multi voltage ballasts are tested ONLY at 120V or 347V (as applicable).

Case: P = Potted, NP = Not Potted      Type: I = Instant start, R = Rapid start, P = Programmed start

IR (Infrared): NT = Not Tested, O = Operates within ranges, Free = IR ranges: 31350-42000 Hz, 53960-59640 Hz