

Commercial Lighting Program

Eligible Product List



*Manitoba Hydro is a licensee of the trademark and Official Mark.

PULSE START METAL HALIDE (MH PS) DIMMABLE FIXTURES (ELECTRONIC BALLASTS)

Manufacturer	Model Number	Type	Lamp Wattage	Voltage	Category	Input Power	Case	Min Start Temp (°C)	Approval Year	Warranty	Comments
Romlight	HBF-20-UV-RP-xx-xx-SH-C3	High Bay	200	120	LH	216	NP	-30	2009	3 yrs	
Romlight	HBF-20-UV-RP-xx-xx-SH-C3	High Bay	200	347	LH	226	NP	-30	2009	3 yrs	
Romlight	HBF-25-UV-RP-xx-xx-SH-C3	High Bay	250	120	LH	270	NP	-30	2009	3 yrs	
Romlight	HBF-32-UV-RP-xx-xx-SH-C3	High Bay	320	120	LH	344	NP	-30	2009	3 yrs	
Romlight	HBF-32-UV-RP-xx-xx-SH-C3	High Bay	320	347	LH	354	NP	-30	2009	3 yrs	
Romlight	HBF-40-UV-RP-xx-xx-SH-C3	High Bay	400	120	LH	426	NP	-30	2009	3 yrs	
Romlight	HBF-40-UV-RP-xx-xx-SH-C3	High Bay	400	347	LH	434	NP	-30	2009	3 yrs	
Romlight	HBF-575-208-277-RP-17A-xx-SH-17L	High Bay	575	347	LH	625	NP	-30	2009	3 yrs	

Case: P = Potted, NP = Not Potted

Category: LH= Low Harmonics (THD<10%), SH= Standard Harmonics (THD<19%)

Multi voltage ballasts are tested ONLY at 120V or 347V (as applicable)

For a complete list of qualifying parameters, contact Manitoba Hydro

**Model Number :

"x" - specifies options, "y" - specifies lamp wattage