

Commercial Lighting Program

Eligible Product List



*Manitoba Hydro is a licensee of the Trademark and Official Mark.

T5 FLUORESCENT LIGHTING SYSTEMS - REGULAR OUTPUT DIMMABLE BALLASTS

Manufacturer	Model Number	Category	Voltage	Input Power	Length	Type	Min Dimming	Case	IR	Test Year	Warranty	Control Type
Lutron	EC5T521J1202	SH	120V	48	2x3'	P	10%	NP	O	2007	5 yrs	3 Wire / DALI
Lutron	EC5T528J1201	SH	120V	34	1x4'	P	10%	NP	O	2007	5 yrs	3 Wire / DALI
Lutron	EC5T528J1202	SH	120V	64	2x4'	P	10%	NP	O	2007	5 yrs	3 Wire / DALI
Lutron	ECO-T528-120-1	SH	120V	28	1x4'	R	10%	P	NT	2009	5 yrs	3 Wire
Lutron	ECO-T528-120-2	SH	120V	56	2x4'	R	10%	P	NT	2009	5 yrs	3 Wire
Lutron	EC5T550JUNV1	LH	120V	54	1x50W PL-L	P	10%	P	NT	2010	5 yrs	3 Wire/DALI
Lutron	EC5T550JUNV1	LH	120V	54	1x4' HO	P	10%	P	NT	2010	5 yrs	3 Wire/DALI
Universal	B128PUNVDV1	LH	120V	32	1x4'	P	1%	NP	NT	2005	3 yrs	DALI
Universal	B214PUNVDV1	LH	120V	35	2x2'	P	1%	NP	NT	2005	3 yrs	DALI

Category: LH= Low Harmonics, SH= Standard Harmonics

Multi voltage ballasts are tested ONLY at 120V or 347V (as applicable).

Case: P = Potted, NP = Not Potted Type: I = Instant start, R = Rapid start, P = Programmed start

IR (Infrared): NT = Not Tested, O = Operates within ranges, Free = IR ranges: 31350-42000 Hz, 53960-59640 Hz