

T5 fluorescent lighting systems high output dimmable ballasts

Manufacturer	Model Number	Category ⁽¹⁾	Voltage [V] ⁽²⁾	Input Power [W]	Lamp	Type ⁽³⁾	Min Temp [°C]	Min Dimming	Case ⁽⁴⁾	IR ⁽⁵⁾	Warranty [years]	Control Type	Approval Year
Lightolier	HDF240T5	LH	120	88	2x3'	P	10	3%	P	NT	3	3 Wire	2010
Lightolier	HDF254T5	LH	120	114	2x4'	P	10	3%	P	NT	3	3 Wire	2010
Lutron	EC5T539J1201	SH	120	46	1x3'	P	10	10%	NP	NT	5	3 Wire / DALI	2007
Lutron	EC5T539J1202	SH	120	92	2x3'	P	10	10%	NP	NT	5	3 Wire / DALI	2007
Lutron	EC5T554J1201	SH	120	60	1x4'	P	10	10%	NP	NT	5	3 Wire / DALI	2007
Lutron	EC5T554J1202	SH	120	120	2x4'	P	10	10%	NP	NT	5	3 Wire / DALI	2007
Lutron	EC5T554JUNV1	SH	120	57.9	1x4'	P	10	10%	P	NT	5	3 Wire	2010
Lutron	EC5T554JUNV2	LH	120	54	2x4'	P	10	10%	P	NT	5	3 Wire/DALI	2010
Lutron	ECDT554C3471	LH	347	62	1x4'	P	10	10%	P	NT	5	3 Wire	2011
Lutron	ECDT554C3472	LH	347	120	2x4'	P	10	10%	P	NT	5	3 Wire	2011
Lutron	ECO T554 120 1	SH	120	62	1x4'	P	10	10%	P	NT	5	3 Wire	2010
Lutron	FDB-T554-120-2	LH	120	132	2x4'	P	10	1%	P	NT	5	3 Wire	2010
Lutron	FDB-T554-120-1	LH	120	69.6	1x4'	P	10	1%	P	NT	5	3 Wire	2010
Sage Lighting	NU254T5D-ROHS	LH	120	120	2x4'	R	10	3%	P	NT	5	0-10V	2010
Universal	B254PUNVDV1	LH	120	126	2x4'	P	10	1%	P	NT	3	DALI	2010
Universal	B154PUNVDV1	LH	120	62	1x4'	P	10	1%	P	NT	5	DALI	2011
Universal	B154PUNVDV1	LH	277	60	1x4'	P	10	1%	P	NT	5	DALI	2011

NOTES:

⁽¹⁾ Category: LH= Low Harmonics, SH= Standard Harmonics

⁽²⁾ Multi voltage ballasts are tested ONLY at indicated voltages.

⁽³⁾ Type: I = Instant start, R = Rapid start, P = Programmed start

⁽⁴⁾ Case: P = Potted, NP = Not Potted

⁽⁵⁾ IR (Infrared): NT = Not Tested, O = Operates within ranges, Free = IR ranges: 31350-42000 Hz, 53960-59640 Hz