

Commercial Lighting Program

Eligible Product List



*Manitoba Hydro is a licensee of the Trademark and Official Mark.

T5 FLUORESCENT LIGHTING SYSTEMS - REGULAR OUTPUT BALLASTS

Manufacturer	Model Number	Category	Voltage	Input Power	Approx Lamp Length	Type	Min Start Temp (°C)	Light Output	Case	IR	Test Year	Warranty
Advance	ICN-2S28	LH	120V	33	1x4'	P	-18	104%	P	NT	2006	5 yrs
Advance	ICN-2S28	LH	120V	64	2x4'	P	-18	103%	P	NT	2006	5 yrs
Etlin-Daniels	ESD-A21T5	LH	120V	24	1x3'	R	-20	99%	P	NT	2009	5 yrs
Etlin-Daniels	ESD-A21T5	LH	120V	48	2x3'	R	-20	91%	P	NT	2009	5 yrs
Etlin-Daniels	ESD-A35T5	LH	120V	36	1x4'	R	-20	107%	P	NT	2009	5 yrs
Etlin-Daniels	ESD-A35T5	LH	120V	69	2x4'	R	-20	91%	P	NT	2009	5 yrs
Future Wave	FWTSD-335P	SH	347V	56	2x5'	R	-18	91%	P	O	2006	5 yrs
Lightolier	HDF228T5	LH	120V	63	2x4'	P	10	98%	P	NT	2010	3 yrs
Sage Lighting	NC235T5	SH	347V	68	1x5'	P	-30	95%	P	NT	2006	5 yrs
Sage Lighting	NC235T5	LH	347V	68	2x4'	P	-30	95%	P	NT	2006	5 yrs
Sage Lighting	NC235T5	LH	347V	80	2x5'	P	-30	95%	P	NT	2006	5 yrs
Standard	E22835T5120-277	LH	120V	35	1x4'	P	-20	107%	NP	Free	2009	5 yrs
Standard	E22835T5120-277	LH	120V	68	2x4'	P	-20	93%	NP	Free	2009	5 yrs
Standard	E22835T5120-277	LH	277V	69	2x4'	P	-20	96%	NP	Free	2009	5 yrs
Ultrasave	ER221120MHT	LH	120V	34	2x2'	P	-29	100%	NP	NT	2009	3 yrs
Ultrasave	ER221120MHT	LH	120V	25	1x3'	P	-29	100%	NP	NT	2009	3 yrs
Ultrasave	ER221120MHT	LH	120V	50	2x3'	P	-29	100%	NP	NT	2009	3 yrs
Ultrasave	ER221347M	LH	347V	50	2x3'	P	-29	100%	NP	NT	2009	3 yrs
Ultrasave	ER221347M	LH	347V	34	2x2'	P	-29	100%	NP	NT	2009	3 yrs
Ultrasave	ER221347M	LH	347V	18	1x2'	P	-29	100%	NP	NT	2009	3 yrs
Ultrasave	ER235120MHT	LH	120V	60	2x4'	P	-29	100%	P	NT	2009	3 yrs
Ultrasave	ER235120MHT	LH	120V	80	2x5'	P	-29	100%	P	NT	2009	3 yrs
Ultrasave	ER235120MHT	LH	120V	30	1x4'	P	-29	100%	P	NT	2009	3 yrs
Ultrasave	ER235347MHT	LH	347V	60	2x4'	P	-29	100%	NP	NT	2009	5 yrs
Ultrasave	ER235347MHT	LH	347V	80	2x5'	P	-29	100%	NP	NT	2009	5 yrs
Ultrasave	SR 132120	SH	120V	32	1x4'	P	0	100%	P	NT	2009	5 yrs

Manufacturer	Model Number	Category	Voltage	Input Power	Approx Lamp Length	Type	Min Start Temp (°C)	Light Output	Case	IR	Test Year	Warranty
Universal	B228PUNV-C	LH	120V	25	1x3'	P	-18	103%	P	NT	2006	5 yrs
Universal	B228PUNV-C	SH	277V	25	1x3'	P	-18	100%	P	NT	2006	5 yrs
Universal	B228PUNV-C	LH	120V	33	1x4'	P	-18	100%	P	NT	2006	5 yrs
Universal	B228PUNV-C	LH	120V	66	2x4'	P	-18	100%	P	NT	2009	5 yrs
Universal	B228PUNV-C	LH	277V	64	2x4'	P	-18	100%	P	NT	2009	5 yrs

Category: LH= Low Harmonics, SH= Standard Harmonics

Multi voltage ballasts are tested ONLY at 120V or 347V (as applicable).

Case: P = Potted, NP = Not Potted Type: I = Instant start, R = Rapid start, P = Programmed start

IR (Infrared): NT = Not Tested, O = Operates within ranges, Free = IR ranges: 31350-42000 Hz, 53960-59640 Hz