

Commercial Lighting Program

Eligible Product List



*Manitoba Hydro is a licensee of the Trademark and Official Mark.

T5 FLUORESCENT LIGHTING SYSTEMS - RETROFIT FIXTURE

Manufacturer	Model Number	Category	Voltage	Input Power	Approx Lamp Length	Type	Min Start Temp (°C)	Light Output	Case	IR	Test Year	Warranty
EcoLight	T5/28FSA	SH	120V	31	1x4'	R	-20	100%	NP	NT	2009	5 yrs
EcoLight	T5/28FSA/C	SH	120V	62	2x4'	R	-20	100%	NP	NT	2009	5 yrs
EcoLight	T5/28FSA/8S	LH	120V	60	2x4'	R	-15	100%	NP	NT	2010	5 yrs
EcoLight	T5/28FAH	SH	347V	31	1x4'	R	-20	100%	NP	NT	2009	5 yrs
EcoLight	T5/54FAH/8R	LH	347V	113	2x4'	R	-15	100%	NP	NT	2010	5 yrs

Category: LH= Low Harmonics, SH= Standard Harmonics

Multi voltage ballasts are tested ONLY at 120V or 347V (as applicable).

Case: P = Potted, NP = Not Potted Type: I = Instant start, R = Rapid start, P = Programmed start

IR (Infrared): NT = Not Tested, O = Operates within ranges, Free = IR ranges: 31350-42000 Hz, 53960-59640 Hz