

## T8 fluorescent lighting systems dimmable ballasts

Manufacturer	Model Number	Category	Voltage [V] <sup>(1)</sup>	Input Power [W]	Lamp	Type <sup>(2)</sup>	Min Temp [°C]	Min Dimming	Case <sup>(3)</sup>	IR <sup>(4)</sup>	Warranty [years]	Control Type	Approval Year
Advance	IZT-132-SC	Premium	120	27	1x3'	P	10	5%	P	NT	5	0-10V	2009
Advance	IZT-132-SC	Premium	120	19	1x2'	P	10	5%	P	NT	5	0-10V	2009
Advance	IZT-132-SC	Premium	120	35	1x4'	P	10	5%	P	NT	5	0-10V	2009
Advance	IZT-132-SC	Premium	277	35	1x4'	P	10	5%	P	NT	5	0-10V	2009
Advance	IZT-2S32-SC	Premium	120	67	2x4'	P	-29	5%	P	NT	5	0-10V	2009
Advance	IZT-2S32-SC	Premium	277	67	2x4'	P	-29	5%	P	NT	5	0-10V	2009
Advance	IZT-3S32-SC	Premium	120	93	3x4'	P	10	5%	P	NT	5	0-10V	2010
Advance	IZT-3S32-SC	Premium	277	93	3x4'	P	10	5%	P	NT	5	0-10V	2010
Advance	IZT-3S32-SC	Premium	120	76	3x3'	P	10	5%	P	NT	5	0-10V	2010
Advance	IZT-3S32-SC	Premium	277	76	3x3'	P	10	5%	P	NT	5	0-10V	2010
Advance	IZT-3S32-SC	Premium	120	54	3x2'	P	10	5%	P	NT	5	0-10V	2010
Advance	IZT-3S32-SC	Premium	277	54	3x2'	P	10	5%	P	NT	5	0-10V	2010
Advance	IZT-4S32	Premium	120	118	4x4'	P	10	5%	P	NT	5	0-10V	2009
Advance	IZT-4S32	Premium	277	116	4x4'	P	10	5%	P	NT	5	0-10V	2009
GE Ultra Max	GE632MAX-H90-V60	Premium	120	221	6x4'	I	-29	60%	P	NT	5	0-10V	2009
Leviton	SD2J8-32M	Premium	120	80	2x4'	P	10	1%	NP	NT	5	0-10V	2010
Leviton	SD1F8-32M	Premium	120	40	1x4'	P	10	1%	NP	NT	5	0-10V	2010
Lightolier	HDF232T8	Premium	120	71	2x4'	P	10	1%	P	NT	3	3 Wire	2010
Lutron	EC5T817J1201	Standard	120	23	1x2'	P	10	10%	NP	NT	5	3 Wire/ DALI	2007
Lutron	EC5T825J1201	Standard	120	29	1x3'	P	10	10%	NP	NT	5	3 Wire/ DALI	2007
Lutron	EC5T825J1202	Standard	120	52	2x3'	P	10	10%	NP	NT	5	3 Wire/ DALI	2007
Lutron	EC5T832J1202	Standard	120	58	2x4'	P	10	10%	NP	Free	5	3 Wire/ DALI	2007
Lutron	H3DT832CUNV210	Premium	120	66.5	2x4'	P	10	1%	P	NT	5	3 Wire	2008
Lutron	H3DT832CUNV210	Premium	277	65.7	2x4'	P	10	1%	P	NT	5	3 Wire	2008
Lutron	H3DT832CUNV310	Premium	120	95.4	2x4'	P	10	1%	P	NT	5	3 Wire	2008
Lutron	H3DT832CUNV310	Premium	277	93.5	2x4'	P	10	1%	P	NT	5	3 Wire	2008
Lutron	FDB-2427-120-2	Premium	120	37	2x2'	P	10	1%	P	NT	5	3 Wire	2010
Lutron	FDB-2427-120-3	Premium	120	51	3x2'	P	10	1%	P	NT	5	3 Wire	2010
Lutron	ECO-T832-120-2-L	Standard	120	64	2x4'	P	10	1%	P	NT	5	3 Wire	2010
Lutron	FDB-4827-120-2	Premium	120	68	2x4'	P	10	1%	P	NT	5	3 Wire	2010
Lutron	FDB-4827-120-1	Premium	120	36	1x4'	P	10	1%	P	NT	5	3 Wire	2010
Lutron	TVE-T832-347-1	Standard	347	38.2	1x4'	P	10	10%	NP	NT	5	0-10V	2010

Manufacturer	Model Number	Category	Voltage [V] <sup>(1)</sup>	Input Power [W]	Lamp	Type <sup>(2)</sup>	Min Temp [°C]	Min Dimming	Case <sup>(3)</sup>	IR <sup>(4)</sup>	Warranty [years]	Control Type	Approval Year
Lutron	TVE-T832-347-2	Standard	347	65.9	2x4'	P	10	10%	NP	NT	5	0-10V	2010
Osram Sylvania	QTP1x32T8/UNV DIM-TC	Premium	120	30	1x4'	P	16	5%	NP	Free	3	0-10V	2007
Osram Sylvania	QTP4x32T8/UNV DIM-TCL	Premium	120	117	4x4'	P	10	5%	P	NT	5	0-10V	2010
Osram Sylvania	QTP4x32T8/UNV DIM-TCL	Premium	120	87	3x4'	P	10	5%	P	NT	5	0-10V	2010
Osram Sylvania	QTP4x32T8/UNV DIM-TCL	Premium	277	112	4x4'	P	10	5%	P	NT	5	0-10V	2010
Osram Sylvania	QTP4x32T8/UNV DIM-TCL	Premium	277	84	3x4'	P	10	5%	P	NT	5	0-10V	2010
Standard	E232PI347-DIM-WTS	Premium	347	64	2x4'	R	0	20%	NP	NT	5	0-10V	2010
Universal	B232PUNVSV3-A	Premium	120	57	2x4'	P	10	3%	P	NT	5	0-10V	2011
Universal	B132PUNVSV3-A	Premium	120	30	1x4'	P	10	3%	P	NT	5	0-10V	2011
Universal	B132R347V5	Premium	347	32	1x4'	R	10	5%	P	NT	5	0-10V	2011
Universal	B232SR347V5	Premium	347	62	2x4'	R	10	5%	P	NT	5	0-10V	2011

## NOTES:

<sup>(1)</sup> Multi voltage ballasts are tested ONLY at indicated voltages.

<sup>(2)</sup> Type: I = Instant start, R = Rapid start, P = Programmed start

<sup>(3)</sup> Case: P = Potted, NP = Not Potted

<sup>(4)</sup> IR (Infrared): NT = Not Tested, O = Operates within ranges, Free = IR ranges: 31350-42000 Hz, 53960-59640 Hz